

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5384)

-----

Set a basalt stone 15x14x6", 10" in the ground for cor. of secs. 22, 23, 26, & 27 mkd with 2 notches on S & E edges, from which

- A fir, 16" dia. bears N.65°E., 51 lks mkd: T28S R1W S23 BT
- A cedar, 14" dia., bears S.10°E., 55 lks., mkd: T28S R1W S26 BT.
- A fir, 12" dia. bears S.24°W., 17 lks mkd: T28S R1W S27 BT
- A fir, 20" dia. bears N.20°W., 65 lks mkd: T28S R1W S22 BT

Bruce A. Shaner - For: Umpqua National Forest - July 15, 1963 - C.S. File 51/259

-----

- Found - Original Basalt Stone, from which a
- 26" D.Fir BT with old face bears N.62°E. 32.0 ft.
  - 24" I.Cedar BT w/scribes vis. bears S.5°E. 33.5 ft.
  - 12" D.Fir BT with scribes visible, now blown down, bears SW 10 ft.
  - 36" D.Fir BT, now blown down, bears NE., 45 ft.
- New BTs-
- 12" D.Fir, I scribed "S27 BT" bears S.81°W., 23.0 ft
  - 38" D.Fir, I scribed "T28S R1W S22 BT" bears N.52°W. 65.4 ft.