

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5389)

-----

Set a basalt stone 15x14x10", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which  
A hemlock, 10" dia., bears S.85°E., 12 lks., mkd: ¼ S11 BT  
A hemlock, 10" dia., bears S.29°W., 23 lks., mkd: ¼ S10 BT

Douglas Co. Surveyors Office - L. E. Monrean - P.L.E. & J.H.C. - 12/1/1975 - C.S. File 57/39-20

-----

Found - 15x14x10" basalt stone set firmly, 10" Deep "¼" marked on west face.  
A Hemlock, 10 (now 11") dia. leaning badly, bears S.85°E., 8.9 ft. (rec. 7.9 ft). Tree scribed "¼ S 11 BT"  
A Hemlock windfall 10" dia. approximate standing position S.29°W., 15.2 ft. tree is rotted, has good blaze.

Set brass cap at 1/4 corner stamped:

COUNTY SURVEYORS OFFICE T28S R1W  
1975 ¼ S10|S11

A Hemlock, 14" dia., bears S.13½°E., 17.7 ft. scribed "¼ S11 CS BT"  
A Hemlock, 11" dia. bears N.62°W., 12.2 ft. scribed "¼ S10 CS BT"