

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 539700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only, T27-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #459, dated June 5, 1883  
-(DCSO records Vol. 11 Page(s) 4770)

-----  
Set post 48x4 ins. firmly in the ground for stan. ¼ sec. cor.  
marked S.C. on N. and S. faces, from which

A Fir 30" dia., bears N.50°E., 43 lks. dist. mkd. SC ¼ S  
BT.

A Fir 30" dia., bears S.10°W., 46 lks. dist. mkd. SC ¼ S  
BT.

GLO survey by Homer D. Angell, Deputy Surveyor, under  
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11  
Page(s) 4774)

-----  
(37.87 chs.)

Old ¼ cor. on line which I destroy.

(40.00 chs.)

Set basalt stone 15x10x10 ins., 10" in ground for ¼ sec. cor.  
marked S C ¼ on N. face, from which

A Hemlock 14" dia., bears NE. 35 lks. dist. mkd. S C ¼ S35  
BT.

A Fir 14" dia., bears S.2°E., 30 lks. dist. mkd. S C ¼ S2  
BT.