

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 578700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, T27-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by S.C. Flint, Contract #459, dated June 5, 1883
-(DCSO records Vol. 11 Page(s) 4770)

Set post 48x4 ins., firmly in the ground for stan. cor. to
secs. 35 and 36 marked S C T27S R1W on N.; S36 on E.; and S35
on W. faces, with 1 notch on E. and 5 on W. edges, from which
A Fir 10" dia., bears N.30°E., 30 lks. dist. mkd. T27S R1W
S36 BT.
A Hemlock 14" dia., bears N.60°W., 71 lks. dist. mkd. T27S
R1W S35 BT.
A Fir 42" dia., bears S.25°W., 55 lks. dist. mkd. S BT.

GL0 survey by Homer D. Angell, Deputy Surveyor, under
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11
Page(s) 4773)

(78.12 chs.)
Old sec. cor. on line which I destroy.
(80.00 chs.)
Set a basalt stone 12x10x6 ins., 8" in ground for stand. cor.
of secs. 35 & 36 marked S C on N. with 1 groove on E. and 5
grooves on W. faces, from which
A Hemlock 30" dia., bears N.46°E., 109 lks. dist. mkd.
T27S R1W S36 BT.
A Hemlock 10" dia., bears N.2°W., 8 lks. dist. mkd. T27S
R1W S35 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew -
Dec. 15, 1969 - C.S. File 54/94-89

Found - 12x10x6 stone, no marks found.
10" now 10" Hemlock, N.2°W., 5.3 ft., scribe visible
30" now 40" Hemlock N.46°E., 72.6 ft., scribe
visible.

Set Brass cap at cor. mkd: County Surveyors Office
T27S R1W S 35 | S 36
T28S S 2
1969

All BTs OK and tagged.
Corner lies about 60 ft. West and 25 ft. South of spring
branch. Also lies 99.0 ft. West of cor. 2|1, T28-1W.