

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5381)  
-----  
Set a basalt stone 12x10x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A fir, 8" dia., bears N.34°E., 55 lks., mkd: ¼ S1 BT.  
A fir, 18" dia., bears S.25°W., 28 lks., mkd: ¼ S12 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-87  
-----  
Found - Stone, right size, firmly in ground, possible ¼ corner.  
8" now 16" D.Fir N.34°E., 36.3 ft., opened for scribing.  
18" now 25" D.Fir S.25°W., 24.6 ft. (Rec. 18.5) shows good scar.  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T28S R1W  
OFFICE S 1  
1969 S 12  
New BT - 14" D.Fir N.87°E., 15.2 ft. mkd: "¼ S1 CS BT"