

PRIMARY CORNER DESCRIPTION SE Cor. S. 36 T27-1; SW Cor. S. 31 T27-1E

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by S.C. Flint, Contract #473, dated June 5, 1883  
-(DCSO records Vol. 11 Page(s) 4771-72)

-----  
Set post 48x4 ins. firmly in the ground for stan. cor. to  
Tps. 27 S., Rs. 1 W. and 1 E. marked S C T27S on N.; R1E S31  
on E.; and R1W S36 on W. faces, 6 notches on N., E., and W.,  
from which

- A Laurel 8" dia., bears N.25°E., 26 lks. dist. mkd. T27S  
R1E S31 BT.
- A Fir 24" dia., bears N.50°W., 194 lks. dist. mkd. T27S  
R1W S36 BT.
- A Laurel 10" dia., bears S.35°W., 25 lks. dist. mkd. S BT.

GLO resurvey by Homer D. Angell, Deputy Surveyor, under  
contract #747, dated May 5, 1902 - (DCSO records Vol. 11  
Page(s) 4771)

-----  
Set post 48x4" firmly in the ground for stan. cor. to Tps. 27  
S, Rs. 1W & 1E mkd S C T 27 S on N, R 1 E S31 on E and R 1 W  
S 36 on W faces - 6 notches on N, E, & W, from which

- A laurel 8" dia., bears N.25°E. 26 lks mkd T27S R1E S31 BT

GLO resurvey by Lincoln E. Wilkes, U.S. Cadastral Engineer;  
Otto L. Draper, U.S. Transitman & Norman D. Price, U.S.  
Transitman, under Special Instructions, dated Dec. 21, 1920  
-(DCSO records Vol. 24 Page(s) 10261)

-----  
The standard cor. of Tps. 27 S., Rs. 1E and 1W. is a badly  
decayed Fir post, 4" sq., 18" above ground, loosely set,  
markings almost obliterated; from which

- A Laurel stump 8" dia., bears N.25°E., 26 lks. dist. no  
markings distinguishable.
- A Laurel stump 10" dia., bears S.35°W., 25 lks. dist., no  
marks distinguishable.

Find no evidence of bearing tree described as a Fir 24"  
dia., bearing N.50°W., 194 lks. mkd. T27S R1W S36 BT.  
Two bark scribed BTs not described in the original field  
notes were found as follows:

- A Fir 7" dia., bears N.40°E., 30 lks. dist. mkd. T27S R1E  
S31 BT.
- A Fir 26" dia., bears N.40°W., 22 lks. dist. mkd. T27S R1W  
S36 BT.

In place of badly decayed post, SET an Iron post 3 ft. long,  
3" dia., 27" in the ground for standard cor., with brass cap  
marked (Cont. Next Page)

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 678700

PRIMARY CORNER DESCRIPTION SE Cor. S. 36 T27-1; SW Cor. S. 31 T27-1E)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

SC  
T27S  
R1W|R1E  
S36|S31  
1927

I blaze and mark new BTs as follows:  
A Fir 7" dia., bears N.40°E., 30 lks. dist. mkd. T27S R1E  
S31 SC BT,  
A Fir 26" dia., bears N.40°W., 22 lks. dist. mkd. T27S R1W  
S36 SC BT.