

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36; & NE Cor. S. 1, T29-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 14 Page(s) 6066)

-----  
Sset a basalt stone 20x12x10 ins., 15" in ground for cor. of Tps. 28 and 29 S., Rs. 1 W., marked with 6 notches on N., S., and W. edges, from which  
A Fir 30" dia., bears S.46°W., 69 lks. dist., mkd. T29S R1W S1 BT.  
A Fir 36" dia., bears N.75°W., 27 lks. dist. mkd. T28S R1W S36 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6154)

-----  
Intersect the cor. of Tps. 28 and 29 S., Rs. 1 W., on the W. bdy. of T28S R1E, which is a basalt stone, 5x12x10 ins. above ground, firmly set, marked with 6 notches on N., S., and W. edges, and witnessed by:  
A Fir 30" dia., bears S.46°W., 69 lks. dist. mkd. T29S R1W S1 BT. (Old BT)  
A Fir 36" dia., bears N.75°W., 27 lks. dist. mkd. T28S R1W S36 BT. (Old BT)

Fd. OK in GLO resurvey by Wilkes; Draper and Price, Survey instructions dated 1920. Found Corner, 1927. Vol. 24, Page 10272