

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5357)

-----  
Set a basalt stone 15x12x6 ins., 10" in ground for ¼ sec. cor. marked ¼ on W. face; from which

A Fir 18" dia., bears S.78°E., 63 lks. dist. mkd. ¼ S31 BT.

A Laurel 10" dia., bears N.12°W., 58 lks. dist. mkd. ¼ S36 BT.

GLO resurvey by Lincoln E. Wilkes, Cadastral Engineer; Otto L. Draper and Norman D. Price, Transitmen - Special Instructions dated Dec. 21, 1920 (Surveyed 1927-1928) - (DCSO records Vol. 24 Page(s) 10273)

-----  
The Cor. established for ¼ cor. of secs. 31 and 36, which is a basalt stone, badly shattered, with the original markings easily distinguishable; from which the original bearing trees:

A Fir 20" dia., bears S.78°E., 63 lks. dist. mkd. ¼ S31 BT. (I obliterate these markings.)

A Laurel 12" dia., bears N.12°W., 58 lks. dist. mkd. ¼ S36 BT.

I now change this cor. to refer to sec. 36 only.

In place of shattered stone, Set a basalt stone 20x8x8 ins., 15" in the ground for ¼ cor. of sec. 36, marked ¼ on W. face; and take new bearing tree as follows:

A Fir 12" dia., bears S.40°W., 44 lks. dist. mkd. ¼ S36 BT