

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5360)

Set a basalt stone 12x10x5 ins., 8" in ground for ¼ sec. cor., marked with ¼ on W. face; from which
A Fir 12" dia., bears N.41°E., 25 lks. dist. mkd. ¼ S18 BT
A Fir 8" dia., bears N.49°W., 21 lks. dist. mkd. ¼ S13 BT.

GLO resurvey by Lincoln E. Wilkes, Cadastral Engineer; Otto L. Draper and Norman D. Price, Transitmen - Special Instructions dated Dec. 21, 1920 (Surveyed 1927-1928) - (DCSO records Vol. 24 Page(s) 10279-80)

The ¼ cor. established for secs. 13 and 18, which is a basalt stone 10x5x4 ins., above ground, firmly set, mkd. ¼ on W. face; from which the original bearing trees
A Fir 15" dia., bears N.41°E., 25 lks. dist. mkd. ¼ S18 BT
A Fir 12" dia., bears N.49°W., 21 lks. dist. mkd. ¼ S13 BT
I now change this cor. to refer to sec. 13 only.
I destroy the markings on bearing tree mkd. for sec. 18 and take new bearing tree as follows:
A Fir 10" dia., bears S.58°W., 34 lks. dist. mkd. ¼ S13 BT