

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5361)

-----  
Set a basalt stone 12x10x6 ins., 8" in ground for ¼ sec. cor. marked ¼ on W. face; from which  
A Fir 16" dia., bears S.15°E., 23 lks. dist. mkd. ¼ S7 BT  
A Fir 12" dia., bears S.40°W., 54 lks. dist. mkd. ¼ S12 BT

GLO resurvey by Lincoln E. Wilkes, Cadastral Engineer; Otto L. Draper and Norman D. Price, Transitmen - Special Instructions dated Dec. 21, 1920 (Surveyed 1927-1928) - (DCSO records Vol. 24 Page(s) 10281-82)

-----  
The ¼ cor. established for secs. 7 and 12, which is a basalt stone 8x5x4 ins., above ground, firmly set mkd. ¼ on W. face; from which the original bearing trees  
A Fir 24" dia., bears S.12°E., 26 lks. dist. mkd. ¼ S7 BT.  
A Fir 18" dia., bears S.44°W., 55 lks. dist. mkd. ¼ S12 BT  
I now change this cor. to refer to sec. 12 only.  
I destroy the markings on bearing tree mkd. for sec. 7 and take new bearing tree as follows:  
A Fir 18" dia., bears N.8°W., 51 lks. dist. mkd. ¼ S12 BT.