

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION CC for T28-1W(NE cor S1) & NW S6, T28-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5362)

Set a basalt stone 15x10x8 ins., 10" in ground for closing cor. of T28S R1W marked CC on N. and with 6 notches on S. and E. edges, from which

- A Fir 18" dia., bears S.80°W., 24 lks. dist. mkd. T28S R1W S1 BT.
- A Fir 12" dia., bears S.45°E., 100 lks. dist. mkd. T28S R1E S6 BT.

GLO resurvey by Lincoln E. Wilkes, Cadastral Engineer; Otto L. Draper and Norman D. Price, Transitmen - Special Instructions dated Dec. 21, 1920 (Surveyed 1927-1928) - (DCSO records Vol. 24 Page(s) 10283)

The closing cor. of Ts. 28 S., Rs. 1 E. and 1 W., which is a basalt stone 10x8x5 ins., above ground, firmly set, marked CC on N. and 6 grooves on E. and W. faces (Rec. S & E), from which the original bearing trees

- A Fir 12" dia., bears S.45°E., 100 lks. dist., mkd. T28S R1E S6 BT.
- A Fir 18" dia., bears S.80°W., 24 lks. dist. mkd. T28S R1W S1 BT.

This closing township cor. is 95 ft. above the standard cor. of Tps. 27 S., Rs. 1 E. and 1 W.
From this closing township cor., the standard corner of Tps. 27 S., Rs. 1 E. and 1 W. bears West, 2.11 chs. dist.