

TOWNSHIP 28 RANGE 02E POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10443  
-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 29, 30, 31, & 32, with brass cap mkd

T28S R2E  
S 30|S 29  
S 31|S 32  
1926

from which

- A fir, 10" dia., bears N.58°E., 20 lks., mkd: T28S R2E S29  
BT.
- A fir, 30" dia., bears S.80°E., 48 lks., mkd: T28S R2E S31  
BT.
- A fir, 15" dia., bears S.24°W., 28 lks., mkd: T28S R2E S31  
BT.
- A fir, 14" dia., bears N.24°W., 21 lks., mkd: T28S R2E S30  
BT.