

TOWNSHIP 28 RANGE 02E POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10446-7

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 19, 20, 29, & 30, with brass cap mkd

T28S R2E  
S 19 | S 20  
S 30 | S 29  
1927

from which

- A fir, 8" dia., bears N.11°E., 22 lks., mkd: T28S R2E S20 BT.
- A cedar, 10" dia., bears S.5°E., 37 lks., mkd: T28S R2E S29 BT.
- A cedar, 12" dia., bears S.48°W., 44 lks., mkd: T28S R2E S30 BT.
- A fir, 12" dia., bears N.49°W., 47 lks., mkd: T28S R2E S19 BT.