

TOWNSHIP 28 RANGE 02E POINT IDENTIFIER # 207700

PRIMARY CORNER DESCRIPTION Cor Secs 31 & 32 only; T27-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10371

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for standard cor. of secs. 31 & 32, with brass cap mkd:

SC  
T27S | R2E  
S 31 | S 32

1927

from which

A fir, 20" dia., bears N.49°E., 61 lks., mkd: T27S R2E S32  
SC BT.

A fir, 24" dia., bears N.56½°W., 112 lks., mkd: T27S R2E  
S31 SC BT.

-----  
Note: GLO Survey by Samuel C. Flint, Under Contract #473, dated June 5, 1883 (DCSO Records Vol. 24 Page(s) 10357) for corner destroyed by Lincoln Wilkes (page 10370)