

TOWNSHIP 28 RANGE 02E POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10437  
-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap mkd

T28S	R2E
S 8	S 9
S 17	S 16

1927

from which

- A fir, 18" dia., bears N.52°E., 4 lks., mkd: T28S R2E S9 BT.
- A fir, 12" dia., bears S.52°E., 37 lks., mkd: T28S R2E S16 BT.
- A pine, 12" dia., bears S.83°W., 22 lks., mkd: T28S R2E S17 BT.
- A pine, 16" dia., bears N.4½°W., 67 lks., mkd: T28S R2E S8 BT.