

TOWNSHIP 28 RANGE 02E POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10412  
-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 10, 11, 14, & 15, with brass cap mkd

T28S R2E  
S 10|S 11  
S 15|S 14  
1927

from which

- A fir, 7" dia., bears N.62°E., 24 lks., mkd: T28S R2E S11  
BT.
- A fir, 30" dia., bears S.80°E., 84 lks., mkd: T28S R2E S14  
BT.
- A fir, 48" dia., bears S.58°W., 10 lks., mkd: T28S R2E S15  
BT.
- A fir, 8" dia., bears N.34°W., 39 lks., mkd: T28S R2E S10  
BT.