

TOWNSHIP 28 RANGE 02E POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10415  
-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 2, 3, 20, & 11, with brass cap mkd

T28S	R2E
S 3	S 2
S 10	S 11
1927	

from which

- A fir, 36" dia., bears N.72°E., 39 lks., mkd: T28S R2E S2 BT.
- A fir, 10" dia., bears S.20°E., 48 lks., mkd: T28S R2E S11 BT.
- A fir, 26" dia., bears S.53°W., 31 lks., mkd: T28S R2E S10 BT.
- A fir, 28" dia., bears N.43°W., 63 lks., mkd: T28S R2E S3 BT.