

TOWNSHIP 28 RANGE 02E POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Cor Secs 35, 36; 1 & 2 T29-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 24 & 25 Pages 10368 & 10705 (duplicate))

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 1, 2, 35, & 36, with brass cap mkd

T28S	R2E
S 35	S 36
S 2	S 1
T29S	
1926	

from which

- A madrona, 7" dia., bears N.59°E., 63 lks., mkd: T28S R2E S36 BT.
- A D.Fir, 20" dia., bears S.83°E., 115 lks., mkd: T29S R2E S1 BT.
- A Y.Pine, 12" dia., bears S.73½°W., 306 lks., mkd: T29S R2E S2 BT.
- A Y.Pine, 20" dia., bears N.45°W., 81 lks., mkd: T28S R2E S35 BT.