

TOWNSHIP 28 RANGE 02E POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10395-6

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 23, 24, 25, & 26, with brass cap mkd

T28S R2E
S 23 | S 24
S 26 | S 25
1926

from which

- A fir, 20" dia., bears N.14°E., 94 lks., mkd: T28S R2E S24 BT.
- A fir, 22" dia., bears S.77°E., 32 lks., mkd: T28S R2E S25 BT.
- A fir, 12" dia., bears S.5½°W., 61 lks., mkd: T28S R2E S26 BT.
- A fir, 48" dia., bears N.26°W., 114 lks., mkd: T28S R2E S23 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Nov. 14, 1966 - C.S. File 54/35-1

Found - 14" I. Pipe at Corner.
20" D.Fir, now stump, N.14°E., 62.7 ft., Opened for scribe "B".
48", now 448" D.Fir, N.26°W. 75.2 ft., shows good scar.

BTs to the south fail in logging road.

Set - Brass Cap at cor. mkd: County Surveyors Office, 1966
T28S R2E
S 23 | S 24
S 26 | S 25

New BTs- 7" D.Fir N.15°E., 41.2 ft. mkd. T28S R2E S24 CS BT.
34" Cedar S.85°W., 56.5 ft. mkd. T28S R2E S26 CS BT.
39" Cedar S.68°E., 165.7 ft. mkd. T28S R2E S25 CS BT

Note - This corner lies north of jogging road 40.0 ft.