

TOWNSHIP 28 RANGE 02E POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10396-7

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 24
S 25
1926

from which

A cedar, 10" dia., bears N.44°E., 39 lks., mkd: 1/4 S24 BT.
A fir, 18" dia., bears S.14°E., 29 lks., mkd: 1/4 S25 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Nov. 14, 1966 - C.S. File 54/35-2

Found - GLO Brass Cap at 1/4 Cor., properly mkd. (1926)
10" Cedar, now 26", N.44°E. 25.7 ft., scribe visible "S".
18" D.Fir, now 20", S.14°E., 19.1 ft., shows good scar.

New BT - 21" Cedar S.74°W., 36.8 ft. mkd. 1/4 S25 CS BT.

Note - This corner lies North of Trail, 15.0 ft.