

PRIMARY CORNER DESCRIPTION SE Township Corner

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10698)

Set an iron post, 3 ft. long, 3" dia., 27" in the ground for cor. of Tps. 28 & 29 S., Rs. 2 & 3 E., with brass cap mkd:

T28S
R2E | R3E
S 36 | S 31
S 1 | S 6
T29S
1926

from which

- A maple, 12" dia., bears N.67°E., 53 lks., mkd: T28S R3E S31 BT.
- A cedar, 10" dia., bears S.38½°E., 116 lks., mkd: T29S R3E S6 BT.
- A W.Fir, 20" dia., bears S.10°W., 12 lks., mkd: T29S R2E S1 BT.
- A maple, 15" dia., bears N.37°W., 6 lks., mkd: T28S R2E S36 BT.

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Group No. 64, surveyed May/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10779)

The cor. of Tps 28 & 29S, Rs 2 & 3 E, which is an iron post, 3" in dia 9" above the ground, with brass cap mkd & witnessed as described in the field notes of the orig. survey.