

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 cor. for Sec. 31; & 36, T28-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5427)

-----  
Set granite stone 8x10x15 ins., 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W. face, from which  
A Fir 10" dia., bears S.79°E., 27 lks. dist. mkd. 1/4 S31 BT.  
A Fir 7" dia., bears S.66°W., 6 lks. dist. mkd. 1/4 S36 BT

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell & Wm. Stoffel, crew - Aug/Sept. 1962 - C.S. File 52/126-1

-----  
Found stone at corner and BTs, all as recorded. SW BT has previously been opened, shows good scribing.  
Set Brass cap at cor. mkd: County Surveyors Office  
(BC set alongside cor. stone) T 28 S  
1/4  
R3W S 36 | S 31 R2W  
1962  
New BT - 13" R.Fir bears S.41°W., 10.0 ft. scribed 1/4 S36 CS BT.

Brent Knapp, i.e. engineering - Crew: N. Fromdahl, J. Ogden, and L. Heddens - 9/2022 - C.S. File 65/111-13

-----  
Found - Brass Cap with stone (properly mkd)  
14" Fir, S79°E, 17.8', down  
New - 9" Cedar, N.25°(E). 9.1', scribed "1/4 S31 BT"  
16" Cedar, S.24°E., 30.3', scribed "1/4 S31 BT"  
39" D.Fir, N.51°W., 10.2', scribed "1/4 S36 BT"  
5" Cedar, N.25°W., 11.2', scribed "X"  
Note - Compass decl. 15°E.