

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; & 25, T28-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5428)

-----  
Set granite stone 8x12x14 ins., 10" in the ground for ¼ sec. cor. marked ¼ on W. face, from which  
A Fir 48" dia., bears S.41°E., 40 lks. dist. mkd. ¼ S30 BT  
A Fir 30" dia., bears N.82°W., 47 lks. dist. mkd. ¼ S25 BT

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell & Wm. Stoffel, crew - Aug/Sept. 1962 - C.S. File 52/126-2

-----  
Found orig. SE. BT, shows good scribing. We also find placed stone at corner, checks record size but do not find chiseled marks. Do not find orig. NW. bearing tree.  
Set brass cap alongside corner stone and marked:  
County Surveyors Office  
T 28S  
¼ R3W S25 | S 30 R2W  
1962  
New BTs- 10" Hemlock bears North 15.4 ft. scribed ¼ S25 CS BT  
7" Hemlock bears S.24°E., 6.6 ft. scribed ¼ S30 CSBT

Fd. BC & 2 BTs & set 6' steel post 2' North by D.Edwards, 4/2011 - C.S. File 65/74-6