

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 100434

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only, T28-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882
- (DCSO records Vol. 13 Page(s) 5425)

Set Laurel post for ¼ sec. cor. 3 ft. long, 3" sq., 24" in
the ground marked ¼ S on E. and W. faces, from which
A Fir 30" dia., bears S.70°E., 55 lks. dist. mkd. ¼ S BT.
A Fir 40" dia., bears S.65°W., 40 lks. dist. mkd. ¼ S BT.

Survey by Ronald A. Quimby, LS #1654, BHW Engineering - For:
U.S. Forest Service - March 1980 - M 83-19

Set 2½" I.P. with brass cap mkd. RLS 1654 T28S R3W ¼ S13 T28S
R2W 1980", from which new BTs:
7" Hemlock N.40°W., 10.0 ft. "E ¼ S13 BT"
9" Madrone S.85°E., 7.2 ft. "E ¼ S13 BT"
Brass washers in BT faces, "RLS 1005".

Survey by Gerald V. Nygren, LS #1035 - For: U.S. Forest
Service - Dec. 12, 1988 - C.S. File 63/92-2

Found - 2½" I.P. with brass cap extending 8" above ground
mkd. "RLS 1005 T28S R3W ¼ S13 | T28S R2W 1980".
(Previous renewal and M 83-19 says cap mkd. RLS
1654)
7" Hemlock bears N.40°W., 10.1 ft., visible scribing
9" Madrona snag bears S.85°E., 7.2 ft., visible
scribing.
New BT - 5" Cedar bears N.74°E., 11.3 ft. scribed "X BT". A
½" brass washer was set in BT face mkd. "LS 1035"
Bearing tree and monument signs were placed on all BTs
without them and a 6" red band and face blazes were painted
on all bearing trees.