

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 100534

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 12 only, T28-3

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882
- (DCSO records Vol. 13 Page(s) 5424)

Set Maple post 3 ft. long, 3" sq., 24" in the ground for ¼
sec. cor. and mkd. ¼ S on E. and W. faces, from which
A Cedar 12" dia., bears N.55°E., 14 lks. dist. mkd. ¼ S BT
A Cedar 10" dia., bears N.68°W., 43 lks. dist. mkd. ¼ S BT

Thomas E. Shrum, Jr. - For: U.S. Plywood Corp - June 1962 -
M 25-7

Found ¼ corner to section 12 only, T28S R3W.

Ronald A. Quimby, LS 1654 - For: U.S. Forest Service - March
1980 - M 83-19

Found - 1½" I.P. with 1962 DCSO brass cap. (No record)
4" x 4" wood post.
18" Cedar snag, N.71°W., 27.11 ft. visible scribes.
9" Hemlock S.61°W., 9.3 ft., good marks.
New BT - 11" Cedar S.24°E., 8.1 ft. "E ¼ S12 BT" Brass washer
RLS #1005 in BT face.
Set fiberglass post and sign N.45°W., 2.0 ft.