

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, (West)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5477-78)

Set Cedar stake (at intersection point 5.89 chs. N. of 1, 6, 7 and 12) 3 ft. long, 4" sq., 24" in the ground for closing cor. secs. 6 and 7, marked C C T28S R2W on E.; S6 on N.; and S7 on S. face, with 1 groove on N. and 5 grooves on S. face, from which

A Cedar 16" dia., bears N.82°E., 48 lks. dist. mkd. T28S R2W S6 BT.

A Cedar 16" dia., bears S.20°E., 82 lks. dist. mkd. T28S R2W S7 BT.

Thomas E. Shrum, Jr. - For: U.W. Plywood Corp. - June 1962 - M 25-7

Found - 18" Cedar S.21°E., 56.4 ft.

31" Cedar N.84°E., 34.0 ft.

Set 2½" alum. cap and new BTs:

21" Cedar S.28½°E., 42.5 ft.

9" W.Fir N.35°W., 12.5 ft.

7" W.Fir N.62½°E., 44.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell & Wm. Stoffel, crew - Aug. 1962 - C.S. File 52/126-38

Found - Orig. 16" now 30" Cedar N.82°E., 31.7 ft., shows good scribing.

Also find stump hole for orig. SE. BT.

Find ¾" I.Pipe with alum. cap at corner.

1961 BT, 25" Cedar S.29°E., 42.2 ft. scribed T28S R2W S7 BT.

1961 BT, 11" W.Fir N.34°W., 12.4 ft. scribed T28S R3W S1 BT.

1961 BT, 7" Fir N.63°W., 43.0 ft. scribed T28S R2W S6 BT.

Kristian DeGroot - June 1998 - C.S. File 65/20-35

Found - 1" (O.D.) iron pipe, firmly set, projecting 8" above the ground w/2½" dia. alum.cap properly stamped

Note: The aluminum cap is oriented to the East.

from which an OBT:

40" Cedar bears N.83°E., 32.1 ft. with scribe marks

"T28S R2W" visible.(Rec. N82°E, 31.7 ft)

(Cont. next page)

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION CC Secs. 6 & 7 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees by Shrum in 1962:
29" cedar bears S.29°E., 42.6 ft. with illegible
scribe marks visible(Rec. S28°30'E, 42.5')
16" W. fir bears N.35°W., 12.6 ft. with a healed
double blaze (Rec. 12.5 ft.)
14" W. fir bears N.63°E., 41.5 ft. with a healed
double blaze (Rec. N62°30'E, 44.0 ft.)
I paint a 6" red band and BT faces red and nail USFS "BEARING
TREE" and "LAND SURVEY MONUMENT" signs to all bearing trees.