

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 104100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Section 6 only, T29-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6233-34)

Set an iron post 3 ft. long, 1" dia., 26" in the ground for 1/4 sec. cor. of sec. 6 only, with brass cap marked:

1/4 S6
1917

from which

A Fir 14" dia., bears S.14°E., 62 lks. dist., marked 1/4 S6 BT.

A Fir 18" dia., bears S.80°W., 35 lks. dist. marked 1/4 S6 BT.

Douglas Co. Surveyors Office - John M. Powell; J. Heritage; C. Commons, crew - March 14, 1973 - C.S. File 56/25-24

Found - 1917 GL0 brass cap at 1/4 corner.
14" D.Fir, now stump, S.14°E., 40.9 ft., shows good scar.

18" D.Fir now stump, S.80°W., 23.1 ft.
New BTs- 30" Laurel S.63°E., 39.2 ft. scribed 1/4 S6 CS BT.
6" Live Oak S.65°W., 53.4 ft. scribed 1/4 S6 CS BT.