

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5465)

Set lava stone 8x8x12", 8" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which
 A fir, 5" dia., bears S.6°E., 17 lks., mkd: 1/4 S31 BT.
 A laurel, 5" dia., bears N.50°E., 30 lks., mkd: 1/4 S30 BT.

Bruce Shaner - For: Umpqua National Forest - May 13, 1968 - C.S. File 55/74

Orig. Corner set by U.S. Gov't. survey in 1909 & described as follows:
Set lava stone 8x8x12", 8" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which
 A fir, 5" dia., bears S.6°E., 17 lks., mkd: 1/4 S31 BT.
 A laurel, 5" dia., bears N.50°E., 30 lks., mkd: 1/4 S30 BT.
I found a 8x8x12" Stone, no "1/4" visible, from which stone a:
 10" dia. D.Fir, an orig. BT. with scribes "S 31 BT" visible, bears S.6°E. 11.2 ft.
 19" dia. Madrone, Orig. Laurel BT., face badly rotted with portions of scribes "1/4" visible, bears N.64°E. (Rec. N.50°E) distance of 19.8 ft.
At the Orig. Corner Stone I placed a Brass Cap mkd: T28S, R2W, 1/4 S30 & S31, 1968 ORE 4906, and from which Brass Cap a:
 10" dia. Madrone, Orig. laurel BT., face badly rotted with portions of scribes "1/4" visible, bears N.64°E. a dist. of 19.8 ft.
 10" dia. D.Fir, an Orig. BT with scribes "S31 BT" visible, bears S.6°E., 11.2 ft.
 26" Sugar Pine, I scribed "1/4S S30 T28S R2W BT", bears N.88°W., a distance of 10.4 ft.
This corner is approximately 7 chains East of a logging road.

FD. BC & 3 BTs Donald R. Stone - April 1977 M 63-80

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed Aug. 2011 - (DCSO records BLM Plat T28-2W 2012-1 & Vol. 58 Page(s) 22942)

The 1/4 sec. cor. of secs. 30 & 31, perpetuated by Shaner, in 1968, monumented with on iron post, 1 1/4" dia., firmly set, projecting 10" above a collar of stone, (alongside of which is the orig. unmarked basalt stone, 8x11x12" (Rec. 8x8x12"), with brass cap (properly) mkd.
from which the remains of an original BT
 A fir, 10" dia., bears S.6°E., 11.2 ft., with scribe marks S31 BT visible on a partially healed blaze. CONT.

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and the remains of a bearing tree mkd, by Shaner
A decayed pine snag, 27" dia., bears N.89 $\frac{3}{4}$ °W., 11.0 ft.,
with scribe marks $\frac{1}{4}$ S30 T28S R2W visible on an open
blaze.
and a new bearing tree
A fir, 13" dia., bears N.64°E., 13.5 ft., mkd. $\frac{1}{4}$ S30 BT.
Incorporate original stone in collar.
Corner is located 120 ft. W. of a gravel road, 12 ft. wide,
bears N.10°W. and S.20°E., in a curve.

Brent Knapp, i.e. engineering - Crew: N. Fromdahl, J. Ogden,
and L. Heddens - 9/2022 - C.S. File 65/111-14

Found - Brass Cap (properly mkd)
Found lava stone, no visible marks
12" D.Fir, S.06°E., 11.2', Healed scar
27"x8' Sugar Pine snag with visible scribe, N.88°W.,
10.4'
Post with USFS sign, South 4.0'
New - 14" Fir, N.64°E., 13.5', Healed scar
Metal Post, East 2.0'
Note - Compass decl. 15°E.