

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5475)</p> <p>-----</p> <p>Set yew post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S7 on N & 18 on S face; from which</p> <p> A hemlock, 8" dia., bears N.2°W., 6 lks., mkd: ¼ S7 BT.</p> <p> A hemlock, 8" dia., bears S.23°E., 12 lks., mkd: ¼ S18 BT.</p>
<p>Thomas E. Shrum, Jr. - For: US Plywood Corp. - June 1962 - M25-7</p> <p>-----</p> <p>Found - Hem. 17" S.23°W., 8.8 ft.</p> <p>Set - 2½" alum. cap</p> <p> Hem. 16" N.68¼°W., 55.8 ft.</p>
<p>Ronald A. Quimby, LS1654 - For: US Forest Service - April 1980 - C.S. File 58/229</p> <p>-----</p> <p>Found - Alum. cap on iron pipe as renewed by Shrum in 1962.</p> <p> 18" Hemlock N.68°W., 55.8 ft. with visible scribe.</p> <p> No orig. evidence left.</p> <p>New BTs- 12" Hemlock S.7°W., 12.5 ft. scribed ¼ S18 BT.</p> <p> 8" Hemlock N.34°E., 14.5 ft. scribed ¼ S7 BT.</p> <p> Placed brass washers in BT faces.</p>
<p> </p>