

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5478) ----- Set granite stone 12x12x14", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which A laurel, 18" dia., bears N.40°W., 32 lks., mkd: ¼ S6 BT. A fir, 10" dia., bears S.60°E., 22 lks., mkd: ¼ S7 BT.</p>
<p>Thomas E. Shrum, Jr. - For: US Plywood Corp. - June 1962 - M25-7 ----- Found - Mad. 15" dia., N.37½°W., 21.8 ft. Fir 9" dia., S.54°E., 14 ft. Set - 2½" alum. cap Cedar 11" dia., N.56°E., 33.5 ft. Fir 15" dia., S.51°E., 28.2 ft.</p>
<p>Ronald A. Quimby - For: US Forest Service - 3/1980 - M79-37 ----- Found - Alum. cap on 1" iron pipe. 1962 13" cedar, N.56°E., 33.5 ft. visible scribes. 14" D.Fir, S.5°E., 20.3 ft. visible scribes (down) New BT - 20" Cedar S.6°E., 98.0 ft. "¼ S7 BT" brass washer RLS 1654 in BT face. Set fiberglass post and signs 4.0 ft. west & south.</p>
<p>Kris DeGroot, LS 1941 - 6/1998 - C.S. File 65/20-32 ----- Found - 1" iron pipe (O.D.) firmly set, projecting 10" above the ground with a 2½" alum. cap stamped, properly marked, from which 21" Cedar bears N.56°30'E., 33.5 ft. with a healed blaze. (Rec. N56°E) 24" Cedar bears S.6°E., 95.3 ft. w/scribe marks "1/4 S7 BT" visible. (Rec. 98.0 ft.) New - I paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all bearing trees.</p>
<p> </p>