

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Dec. 1968 - M37-17 ----- Set - 2½" dia., alum. cap mkd: USPC PROPERTY CORNER T28S R2W S6 RE 4287 (and corner description) D.Fir 72" dia., N.32°W., 35.4 ft. D.Fir 34" dia., S.81°W., 42,5 ft. Note- BTs mkd: S6 BT RE 4287 (and corner description)	
Ronald A. Quimby, LS 1654 - For: US Forest Service - March 1980 - M79-37 ----- Set - 2½" iron pipe with brass cap mkd: T28S, R2W, C¼ S6, RLS 1005, 1980, from which 13" Hemlock N.7°W., 53.6 ft. "C¼ S6 BT" 26" D.Fir S.70°E., 78.8 ft. "C¼ S6 BT" Brass washer RLS 1005 in bot BT faces. Set post & sign 4.0' North & East. Found - Alum. cap on 1" iron pipe - N.3°44'53"W., 1.93 ft. 72" D.Fir bears N.32°W., 37.2 ft. visible scribes. 34" D.Fir bears S.81°W., 42.5 ft. visible scribes.	
Kris DeGroot, LS 1941 - 6/1998 - C.S. File 65/20-34 ----- Found - 2½" (O.D.) IP, firmly set, flush with the ground with a 2½" brass cap (properly stamped) from which BTs by Quimby & Ware in 1980. 19" Hemlock bears N.7°W., 53.6 ft. with healed double blaze. 33" D.Fir bears S.75°E., 79.3 ft. with a healed double blaze, (rec. S.70°E., 78.8 ft) 1" (O.D.) IP, firmly set, projecting 30" above the ground with a 2½" alum. cap stamped "T28S R2W C¼ S6 RE 4287 1968" bears N.8°30'W., 1.84 ft. (Rec. N.3°44'53"W., 1.93 ft.) BTs by Shrum in 1968 53" D.Fir bears N.32°W., 36.0 ft., with healed blaze. (Rec. N.32°W., 37.2 ft.) 39" D.Fir bears S.82°W., 41.8 ft., with healed blaze (Rec. S.81°W., 42.5 ft.) New - I paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all bearing trees.	