

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 144100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, T29-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCS0 records Vol. 15 Page(s) 6234)

Set a conglomerate stone 15x10x5 ins., 10" in the ground for cor. of secs. 5 and 6, marked with 1 notch on W. and 5 notches on E. edge; from which
A Hemlock 18" dia., bears S.59°E., 28 lks. dist., marked T29S R2W S5 BT.
A Cedar 18" dia., bears S.14°W., 22 lks. dist., marked T29S R2W S6 BT.

Survey by John H. Markham, Jr. - Dec. 12, 1961 - C.S. File 51/221-4

Determined by O.B.T.
26" Hemlock snag bears S.59°E., 18.5 ft., found scribe.
At corner point, Set 1" x 30" I.Pipe, from which
1½" Fir bears N.70°E., 2.6 ft., not marked.
5" Laurel bears S.56°E., 28.0 ft. mkd. S6 R2W BT.
3" Fir bears S.41°E., 19.0 ft. mkd. S5 XX BT.
3" Fir bears S.1°W., 45.5 ft. mkd. S6 BT.
Skid road bears South 35.0 ft.
Corner lies in old logging, a real brush pile.

Douglas Co. Surveyors Office - John M. Powell; J. Heritage; C. Commons, crew - March 14, 1973 - C.S. File 56/25-25

Found - 1" I.Pipe at corner.
3" D.Fir, now 7", S.41°E., 19.0 ft. scribe visible "S5"
3" D.Fir now 8", S.1°W., 45.5 ft., shows scar. NE. and SE. BTs other than the above, cut.
New BT - 7" D.Fir, North 18.1 ft. scribed T28S R2W S31 CS BT
All trees tagged.