

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5430)

Set Cedar stake 3 ft. long, 4" sq., 24" in the ground for cor. secs. 31 and 32, marked T28S S32 on NE.; and R2W S31 on NW. face, with 1 notch on W. and 5 notches on E. edge, from which

A Fir 12" dia., bears N.50°E., 29 lks. dist., marked T28S R2W S32 BT.

A Cedar 5" dia., bears N.72°W., 10 lks. dist., marked T29S R2W S31 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6235)

The cor. of secs. 31 and 32, which is a Cedar post, badly decayed, marked and witnessed as described by the surveyor general. I perpetuate this cor., as follows: alongside the old cor.

Set a basalt stone 12x10x6 ins., 8" in the ground, for cor. of secs. 31 and 32, T28S., R2W. only, marked with 1 notch on the W. and 5 notches on the E. edge; from which

A Fir 12" dia., bears N.50°E., 29 lks. dist., mkd. T28S R2W S32 BT. (Old BT)

A Cedar 5" dia., bears N.72°W., 10 lks. dist., marked T28S R2W S31 BT. (Old BT)