

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5466)

-----  
Set fir stake, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S30 on W., & 29 on E face, from which:  
A pine, 8" dia., bears S.55°W., 14 lks., mkd: ¼ S30 BT.  
A pine, 7" dia., bears N.71°E., 45 lks., mkd: ¼ S29 BT.

Bruce Shaner - For: Umpqua National Forest - May 13, 1968 - C.S. File 55/74

-----  
Orig. corner set by U.S. Gov't survey in 1909 and described as follows:  
Set fir stake, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S30 on W., & 29 on E face, from which:  
A pine, 8" dia., bears S.55°W., 14 lks., mkd: ¼ S30 BT.  
A pine, 7" dia., bears N.71°E., 45 lks., mkd: ¼ S29 BT.  
Orig corner stake was missing but from the spot it occupied a  
10" Pine, orig. BT with scribes visible, now blown down and rotting, bears S.55°W. a distance of 9.2 ft.  
16" W.Pine, orig. BT with scribes visible, bears N.71°E., a distance of 29.7 ft.  
I set a brass cap mkd: "T28S R2W ¼ S30 & S29, 1968, ORE 4906" at position of orig. corner stake from which Brass Cap a:  
10" Pine, orig. BT with scribes visible, now blown down and rotting, bears S.55°W a distance of 9.2 ft,  
16" W.Pine, orig. BT with scribes visible, bears N.71°E a distance of 29.7 ft.  
10" D.Fir, I scribed "¼ S S30 T28S R2W BT", bears S.26°W., a distance of 22.0 ft.

FD. BC & 2 BTs Donald R. Stone - April 1977 M 63-80