TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Pages 5466-7)

Set granite stone 5x8x16", 11" in the ground for cor. of secs. 19, 20, 29, & 30 mkd with 2 notches on S & 5 notches on E edge, from which

A chinquapin, 6" dia., bears N.67°E., 35 lks., mkd: T28S R2W S20 BT.
A fir, 8" dia., bears S.43°E., 23 lks mkd: T28S R2W S29 BT
A fir, 12" dia. bears S.28°W., 31 lks mkd: T28S R2W S30 BT
A pine, 8" dia. bears N.75°W., 24 lks mkd: T28S R2W S19 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Feb. 1968 - C.S. File 54/26-8

Found - 6" Chinq. now stob, N.67°E. 23.1 ft. scribe visible.
8" now 19" D.Fir, S.43°E. 15.2 ft., shows good scar.
12"now 26" D.Fir S.28°W. 20.5 ft., shows good scar.
8" Pine, now dead, N.75°W., 15.8 ft., scribe visible
Stone, firmly set, at corner point.

Set - Brass Cap at Cor. Mkd: County Surveyors Office 1968

T28S R2W

S 19	S 20
S 30	S 29

New BTs- 29" D.Fir N.46½°W. 18.4 ft. mkd. "T28S R2W S19 CS BT
8" Hemlock N.36°E. 23.8 ft. Mkd. T28S R2W S20 CS BT.

Note -This corner lies approx. 25.0 ft. N. of spring branch.