

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec 3, 1908 - (DCSO records Vol. 13 Pages 5469-70)

Set fir post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 17, 18, 19, & 20, marked T28S S 17 on NE, R2W S 20 on SE, S 19 on SW, S 18 on NW faces, with 5 notches on E & 3 notches on S edge; from which

- A fir, 38" dia. bears N.55°E., 53 lks mkd: T28S R2W S17 BT
- A fir, 10" dia. bears S.17°E., 26 lks mkd: T28S R2W S20 BT
- A fir, 8" dia. bears S.59°W., 30 lks. mkd: T28S R2W S19 BT
- A fir, 9" dia. bears N.20°W., 40 lks. mkd: T28S R2W S18 BT

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Joel Sheriff - April 14, 1977 - C.S. File 59/31-26

- Found - No monument found.
- A 9" D.Fir stump bears S.59°W., 19.8 ft. scribing visible "S19 on partly healed blaze.
 - A 16" D.Fir stump bears S.19°E., 17.4 ft. has a healed blaze. (Rec. S.17°E., 17.16 ft.).
 - A 17" D.Fir stump bears N.20°W., 26.61 ft. has a healed blaze (Rec. N.20°W., 26.4 ft.)
 - A 42" D. Fir stump bears N.55°E., 34.98 ft. Has a healed blaze.
- Set - A 2½" brass cap in a mound of stone mkd: County Surveyors Office T28S R2W S18 S17 S19 S20 1977. Set a 6 ft. Iron post alongside with a F.S. 54-4 sign attached. Set brass cap by reference to accessories. (OBTs.)
- New - A 8" Chinquapin bears N.78°E., 105.5 ft. scribed "S17 CS BT" on a double blaze.
- A 7" D.Fir bears S.53°E., 178.0 ft. scribed "T28S R2W S20 CS BT on a double blaze.
 - A 8" Spike in top of 42" Orig. BT stump bears N.55°E., 34.75 ft
 - A 8" Spike in top of 17" Orig. BT stump bears N.20°W., 26.6 ft.
 - A 8" Spike in the top of 17" Fir stump bears N.79°W., 30.3 ft.
 - A 8" Spike in the base of 16" Orig. ST stump bears S.19½°E., 16.75 ft.
- Note - Corner lies approx 100 ft. NW of F.S. Road No. 2817 in a clearcut unit.