

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page 5478A)</p> <p>-----</p> <p>Set granite stone 8x10x15", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which</p> <p> A fir, 3" dia., bears S.65°E., 15 lks., mkd: 1/4 S5 BT.</p> <p> A fir, 3" dia., bears N.50°W., 57 lks., mkd: 1/4 S6 BT.</p>
<p>Thomas E. Shrum, Jr. - For: US Plywood Corp. - Dec. 1968 - M37-17</p> <p>-----</p> <p>Set - 2 1/2" dia., Alum cap mkd: "1/4 S6 S5 USPC Prop Cor. RE4287"</p> <p> 6" dia., D.Fir S.56°W., 12.3 ft. "1/4 S6 RE 4287"</p> <p> 6" dia., D.Fir S.68°E., 10.9 ft. "1/4 S5 RE 4287"</p>
<p>Ronald A. Quimby, LS 1654 - For: US Forest Service - March 1980 - M79-37</p> <p>-----</p> <p>At proportionate location:</p> <p>Set - 2 1/2" iron pipe with brass cap marked T28S R2W 1/4 S6 S5 RLS 1654 1980</p> <p>New - 14" Fir, S.35°W., 25.2 ft. "1/4 S6 BT"</p> <p> 10" Madrone S.64°E., 26.0 ft. "1/4 S5 BT"</p> <p> Brass washers RLS 1005 in both BT faces.</p> <p> Set post 5.0 ft. east.</p> <p>Shrum's corner location bears N.33°40'29"W., 31.51 ft. as computed from SE BT - 10" Fir.</p>
<p>Douglas Co. Surveyors Office - Randall Smith, Deputy - Stephen J. Flause - 10/23/1995 - C.S. File 64/64-6</p> <p>-----</p> <p>Found - 2 1/2" dia. Brass cap on an iron pipe, 6" below with 2 1/2" dia, mound of stone on top.</p> <p> 14" now 16" dia. D.Fir, with partially healed burnt double blaze, illegible scribing visible, bears S.42 1/2°W., 25.2'</p> <p> 10" now 10" dia. 3' high Madrone stump, with a partially healed double blaze scribing visible "1/4 S5 BT" and 1 1/4" dia. brass washer mkd. "RLS 1005" attached to lower blaze, bears S.65 1/2°E., 26'.</p> <p>New BT - 10" dia. D.Fir, double blazed and scribed "1/4 S6 CS BT", bears N.15 1/2°W., 8.5'.</p> <p> 10" dia. D.Fir, double blazed and scribed "1/4 S5 CS BT", bears N.85 1/4°E., 7.9'.</p> <p> 10" dia., D.Fir double blazed and scribed "1/4 S5 CS BT", bears S.15°E., 9.4'.</p>