

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5470)

Set cedar post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S17 on N & 20 on S face; from which
A fir, 5" dia., bears N.25°E., 39 lks., mkd: ¼ S17 BT.
A fir, 48" dia., bears S.22°E., 37 lks., mkd: ¼ S20 BT.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Travis Worthen - July 6, 1977 - C.S. File 59/38-3

Found - No monument
A 15" Hemlock bears N.25½°E., 25.74 ft. has healed blaze.
A 48" D.Fir bears S.23°E., 24.46 ft. has a healed blaze.
Both BTs alive and well. Placed County BT signs on both.
Set - 2½° Brass cap on 1" I.P. stamped County Surveyors Office T28S R2W ¼ S17 S20 1977. Set by reference to orig. BTs.
Place a 18" x 12" x 10" rock mound around Brass cap.
No new accessories.