

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5477)

Set granite stone 6x10x14", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
 A fir, 36" dia., bears N.24°W., 17 lks., mkd: ¼ S5 BT.
 A fir, 30" dia., bears S.40°E., 19 lks., mkd: ¼ S8 BT.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Terrie Plouff - July 13, 1981 - C.S. File 61/27-16

Found - Orig. stone mon. NOT fnd.
 34" Fir (Orig. 30") snag bears S.40°E., 12.5 ft. found bark scribing S8 BT
 Orig. NW BT NOT fnd...An approximate 4-ft. dia. hole bears N.30°W., 8.3 ft. (REC to orig. BT is N.24°W., 11.2 ft.)
Set - As the scribed SE BT is the only good evidence remaining of the orig. corner monument or accessories, at record bearing & distance from the S.E. BT, we set a 1"x36" IP, with Brass Cap attached on bedrock with mound of stone; Cap is stamped Douglas Co. Surveyor T28S R2W ¼ S5 S8 1981
New BTs- 48" D.Fir, bark scribed ¼ S8 CS BT bears S.83°W., 16.6 ft.
 10" D.Fir, blazed & scribed ¼ S5 CS BT bears N.17°W., 22.8 ft.
 12" D.Fir, blazed & scribed ¼ S8 CS BT bears S.56°E., 28.4 ft.
 40" D.Fir, bark scribed ¼ S8 CS BT bears S.27°E., 26.4 ft.
NOTE - This corner lies on a steep SW slope with shallow soil bedrock.