

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 242700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T27-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Romanso E. Ware and Ronald A. Quimby - For: U.S. Forest Service - July 1980 - M 79-49

Set 2½ Iron pipe with brass cap marked "T27S R2W 1/4 S32 RLS 1654 1980", from which

7" W.Fir bears N.47°W., 23.5 ft. mkd. "¼ S32 BT"

12" W.Fir bears N.28°E., 27.4 ft. mkd. "¼ S32 BT"

Brass washer mkd. "RLS 1654" set in BT faces.
set post and sign 5.0 ft. North.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 21981-2)

The ¼ sec. cor. of sec. 32 only, established at midpoint bet. the closing cors. of secs. 32 and 33, and secs. 31 and 32, by Ware and Quimby in 1980, and is accepted as the cor.; monumented with an iron post, 2" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.

from which the remains of BTs mkd. by Ware and Quimby

A fir, 16" dia., bears N.30¾°E., 27.1 ft., with a healed blaze.

A fir snag, 7" dia., bears N.47¼°W., 23.2 ft., with scribe marks ¼ S32 BT visible on an unhealed double blaze.

and new bearing tree

A fir, 27" dia., bears N.52°W., 39.1 ft., mkd. ¼ S32 BT.