

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5431)

Set granite stone 5x8x15 ins., 10" in the ground for cor. secs. 32 and 33, marked with 4 notches on E. and 2 notches on W. edge, from which
 A Fir 10" dia., bears N.47°E., 9 lks. dist., marked T28S R2W S33 BT.
 A Fir 8" dia., bears N.54°30'W., 15 lks. dist., marked T28S R2W S32 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6236)

The cor. of secs. 32 and 33, which is a granite stone, firmly set, marked and witnessed as described by the surveyor general.

Douglas Co. Surveyors Office - John Powell and crew - July 1971 - C.S. File 54/26-1A

Looked for, not found. This area logged also BTs were small 8" and 10".