TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5452)

Set hemlock post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 28, 29, 32, & 33, marked T28S S 28 on NE, R2W S 33 on SE, S 32 on SW, S 29 on NW face, with 1 notch on S & 4 notches on E edge; from which

A fir, 16" dia. bears N.36°E., 13 lks mkd: T28S R2W S28 BT
A hemlock, 8" dia., bears S.28°E., 34 lks., mkd: T28S R2W S33 BT.
A fir, 7" dia., bears S.9°W., 35 lks. mkd: T28S R2W S32 BT
A hemlock, 8" dia., bears N.55°W., 16 lks., mkd: T28S R2W S29 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & Crew - May 18, 1968 - C.S. File 54/26-7

Found - Orig. 8" now 15" hemlock S.28°E., 22.4 ft. Open from backside & find "R2W S33 BT" scribe & reverse.
Orig. 16" now 30" Fir N.36°E., 8.5 ft. shows good scar. We do not open.
NW & SW BTs are gone.

Set - Brass cap mkd: County Surveyors Office 1966 T28S $\frac{\text{S 29} \mid \text{S 28}}{\text{S 32} \mid \text{S 33}}$ R2W

New BTs- 15" hemlock S.28°E., 22.4 ft. (Orig. BT) mkd: T28S R2W S33 CS BT.
20" D.Fir S.8°W., 13.7 ft. mkd: T28S R2W S32 CS BT.
24" D.Fir N.52°W., 50.8 ft. mkd: T28S R2W S29 CS BT.

Brent Knapp - For: Umpqua Indian Forest Management, LLC - 9/2021 - M179-80

Found - Brass cap
36" Fir with healed scar bears N.36°E., 8.5'
15'x22" snag with healed scar bears S.8°W., 13.7'
30" Fir with healed scar bears N.52°W., 50.8'
12'x9" Fir snag with USFS tag and no scribe bears S.47°W., 14.6' (no record)

Set - A metal post bears S.50°E., 4.2'
A metal post bears S.32°W., 6.9'
A metal post bears N.52°W., 4.4'
A metal post bears N.37°E., 4.0'