

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20, 21, 28, & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5454)

Set yew post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 20, 21, 28, & 29, marked T28S S 21 on NE, R2W S 28 on SE, S 29 on SW, S 20 on NW faces, with 4 notches on E & 2 notches on S edge; from which

A cedar, 12" dia., bears N.26°E., 13 lks., mkd: T28S R2W S21 BT.

A yew, 10" dia. bears S.33°E., 26 lks mkd: T28S R2W S28 BT

A cedar, 18" dia., bears S.42°W., 51 lks., mkd: T28S R2W S29 BT.

A hemlock, 18" dia., bears N.73°30'W., 73 lks., mkd: T28S R2W S20 BT.

Douglas Co. Surveyors Office - John Powell - W. Penley & J. Heritage - 2/10/1971 - C.S. File 54/26-2

Found - 12" now 16" cedar, N.26°E., 8.6 ft. scribe visible.
10" yew now down, S.33°E., 17.2 ft. scribe visible.
18" cedar, now dead, S.42°W., 33.7 ft scribe visible
No trace of NW BT

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T28S R2W
OFFICE S 20 | S 21
1971 S 29 | S 28

New BTs- 15" hemlock N.9°W., 49.3 ft. scribed "T28S R2W S20 CS BT.
6" hemlock S.9°E., 51.5 ft. scribed "T28S R2W S28 CS BT.
22" hemlock S.11°W., 70.0 ft. scribed "T28S R2W S29 CS BT.