

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5456)

Set granite stone 5x12x16", 11" in the ground for cor. of secs. 16, 17, 20, & 21 mkd with 3 notches on S & 4 notches on S & 4 notches on E edges, from which

- A fir, 8" dia. bears N.54°E., 94 lks. mkd: T28S R2W S16 BT
- A fir, 14" dia. bears S.44°E., 3 lks. mkd: T28S R2W S21 BT
- A fir, 10" dia., bears S.17°45'W., 21 lks., mkd: T28S R2W S20 BT.
- A hemlock, 8" dia., bears N.46°W., 45 lks., mkd: T28S R2W S17 BT.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Travis Worthen - Sept. 2, 1977 - C.S. File 59/40-3

Found - 3"x7"x16" stone lying on ground surface with 3 distinct notches on one edge.

- 21" D.Fir (orig. 8") N.54°E., 62.04 ft. Has a healed blaze.
- 14" D.Fir (orig. 8" hemlock) bears N.46°30'W., 29.7 ft. has a healed blaze.
- 17" D.Fir (Orig. 10") bears S.22°30'W., (Rec. S.17°45'W.) 13,86 ft. has a healed blaze.
- 20" D.Fir (orig. 14") bears S.44°E., 1.98 ft. has a healed scar.

All are alive & well-placed county BT signs on all four trees
Set - 2½" brass cap stamped COUNTY SURVEYORS OFFICE

T28S	R2W
<u>S 17</u>	<u>S 16</u>
<u>S 20</u>	<u>S 21</u>
1977	

No new accessories. Corner lies on a steep SE slope.