

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5460)  
 -----  
 Set granite stone 8x12x14", 10" in the ground for cor. of secs. 4, 5, 8, & 9 mkd with 5 notches on S & 4 notches on E edge, from which  
 A fir, 36" dia. bears N.19°E., 21 lks. mkd: T28S R2W S4 BT  
 A fir, 36" dia. bears S.15°E., 63 lks. mkd: T28S R2W S9 BT  
 A hemlock, 6" dia., bears S.37°W., 61 lks., mkd: T28S R2W S8 BT.  
 An alder, 6" dia., bears N.51°W., 36 lks., mkd: T28S R2W S5 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - May 7, 1968 - C.S. File 54/26-5  
 -----

Found - Orig. corner stone 14x12x8" in place & mkd with 5 notches on South & 4 notches on East sides about 3" under duff.  
 Orig. 6" alder, now only badly decayed remains N.41°W., 25.1 ft. (Rec. N.51°W. 23.8 ft) find fragmentary reverse scribe.  
 Orig. 6" now 18" Hemlock, S.40°W., (Rec. S.37°W.) 40.3 ft. alive, shows good scar. We do not open. Rescribe "T28S R2W S8 CS BT"  
 Orig. 36" now 42" Fir, S.72°E., 13.9 ft. (Rec. S.15°E., 41.6 ft.) alive - we open & find "S R2W S9 B" scribe.  
 Orig. 36" now 44" fir, alive, N.66°E., 41.6 ft. (rec. N.19°E., 13.9') We open & find "SR2W S4 BT" scribe.

All face measurement.  
 Set - At corner in place of stone, set:  
 Brass cap at cor. mkd: COUNTY SURVEYORS T28S R2W  
 OFFICE S 5 | S 4  
 1968 S 8 | S 9

New BTs- 10" hemlock N.54°E., 15.7 ft. mkd: T28S R2W S4 CS BT  
 9" Hemlock N.17°W., 32.5 ft. mkd: T28S R2W S5 CS BT  
 6" Hemlock S.23°E., 11.6 ft. mkd: T28S R2W S9 CS BT

Note - Creek calls S & E fit good.