

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 301700

PRIMARY CORNER DESCRIPTION A P on No bdy Sec 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by S.C. Flint, Contract #459, dated August 3, 1882  
- (DCSO records Vol. 12 Page(s) 4864)

-----  
Set Cedar post 4 ft. long, 4" sq., 24" in the ground for  
standard cor. to secs. 32 and 33 and marked S C T27S R2W on  
N.; S33 on E.; and S32 on W. faces, with 4 notches on E. and  
2 on W. faces, from which  
    A Fir 16" dia., bears N.45°E., 9 lks. dist. mkd. T27S R2W  
        S33 BT.  
    A Fir 16" dia., bears N.25°W., 5 lks. dist. mkd. T27S R2W  
        S32 BT.  
    A Fir 16" dia., bears S.30°W., 98 lks. dist. mkd. T28S R2w  
        S5 BT.

GL0 Resurvey by Morris Wygant, Compassman for Zachariah  
Derrick, U.S. Deputy Surveyor, Under Contract #779, dated  
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4905)

-----  
The stand. cor. of secs. 32 and 33, which is a post, firmly  
set, marked and witnessed as described by the surveyor  
general, bears N. 25 lks. dist. I now change this cor. to an  
Angle Point as follows:  
Cut out all marks, and mark AP on N. face; then cut out all  
BTs and remark AP BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
June 12, 1969 - C.S. File 54/40-170

-----  
Found - Unrecorded 3/4" I.P. set from OBTs. as follows.  
    Orig. 16" now 28" Fir, N.45°E., 5.9 ft., alive, old  
        bark blaze, no scribe found.  
    Orig. 16" now 30" Fir, N.25°W., 3.3 ft., alive,  
        chopped open and burned possible scribe marks.  
    Orig. 16" now 28" Fir, S.30°W., 64.7 ft., alive, old  
        bark blaze, fragmentary scribe mark found.  
    Also found O.B.T., unrecorded, 32" Fir S.27°E., 11.4  
        ft., alive, shows scar of approx. same age as NW.  
        BT.  
Did Not Set Brass Cap.  
New BTs- 13" D.Fir N.17°W., 11.2 ft. mkd. AP CS BT.  
        28" D.Fir N.45°E., 5.9 ft. mkd. AP CS BT.  
The closing cor. of secs. 4 & 5, T28-2, bears West, 96.3 ft.

Survey by Romano E. Ware and Ronald Quimby - For: U.S.  
Forest Service - July 1980 - M 79-49

-----  
Found - 3/4" Iron pipe.

(Cont. Next Page)

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 301700

PRIMARY CORNER DESCRIPTION A P on No Bdy Sec 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

30" D.Fir N.45°E., 5.9 ft, visible bark scribe.  
32" D.Fir N.25°W., 3.3 ft., good scar.  
34" D.Fir S.27°E., 11.4 ft., good scar.  
13" D.Fir N.17°W., 11.2 ft., good scar.  
Set 2½" Iron pipe with brass cap mkd. "T27S R2W AP S32 S4  
T28S RLS 1654 1980", over top of found I.P.  
Set post and sign #54-9, 2.0 ft. East.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore,  
Cadastral Surveyors & Robert H Browning, Survey Technician,  
under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO  
records Vol. 56 Page(s) 21980)

-----  
At an Angle point bet. secs. 32 & 4, on the S. bdy. of the  
Tp., originally established as the Standard Cor. of secs. 32  
and 33, in 1882, perpetuated by the Douglas County Surveyors  
Office in 1969 and remonumented by Ware and Quimby in 1980,  
monumented with an iron post, 2" dia., firmly set, projecting  
11" above ground, with brass cap (properly) mkd.  
from which the remaining original bearing trees  
A fir, 33" dia., bears N.45°E., 7.4 ft. with scribe marks  
AP CS BT visible in the bark over a healed blaze.  
(Record, 5.9 ft.)  
A fir, 32" dia., bears N.25°W., 3.3 ft., with fragmentary  
scribe marks visible on an opened blaze.  
and a BT mkd. by the Douglas County Surveyors Office  
A fir, 13" dia., bears N.18°W., 11.3 ft., with a healed  
blaze.  
and bearing tree mkd. by person(s) unknown  
A fir, 35" dia., bears S.29¼°E., 11.2 ft., with a healed  
blaze.