

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 303700

PRIMARY CORNER DESCRIPTION C C for Secs. 32 and 33 only, T27-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4946)

Intersect South bdy. of Tp 298 lks. S.89°39'E. of old cor for secs 32 & 33, which I previously changed to an Angle Point
At point of intersection, I mark a Fir tree, 16" in dia., for closing cor. of secs. 32 and 33, marked CC T27S R2W on N.; S32 on W.; and S33 on E. side, with 4 grooves on E. and 2 grooves on W. sides, from which

A Fir 24" dia., bears N.36°50'E., 35 lks. dist. mkd. T27S R2W S33 BT.

A Fir 24" dia., bears N.55°40'W., 37 lks. dist. mkd. T27S R2W S32 BT.

Douglas Co. Surveyors Office - Gary L. Langlitz; E.D. Hartin; G.E. Quibell, crew - May 29, 1974 - C.S. File 56/51-13

Found - Orig. 16" now 24" D.Fir at the closing cor., with a well healed blaze and 4 notches on the E. side and well healed blazes on the N. and W. sides.
We do not open.

Orig. 24" now 26" D.Fir, N.44°E., 23.1 ft. (Rec. N.36°50'E., 23.1 ft.) showing a well healed blaze

Orig. 24" now 30" D.Fir bears N.59°W., 25.1 ft. (Rec. N.55°40'W., 24.4 ft.) with scribing "T27S R2W" visible on previously opened blaze. (Note: the orig. dist. appears to have been measured to the scribed face of the BT)

We do not Monument.

Survey by Romanso E. Ware and Ronald A. Quimby - For: U.S. Forest Service - July 1980 - M 79-49

Found - Orig. Corner tree, 7.0 ft. S.0°0'45"E., 26" D.Fir with healed blazes and 4 notches on the E. side and healed blazes on the N. and W. sides.

26" D.Fir N.44°E., 23.1 ft., good scar.

32" D.Fir N.59°W., 25.1 ft., good scar.

Set 2½" Iron pipe with brass cap mkd. "T27S R2W WC CC S32 S33 S4 T28S R2W 1980 RLS 1005", South 7.0 ft.

New BTs- 12" D.Fir S.50°E., 12.4 ft. "W.C. T27S R2W S32 S33 BT"
Rescribed 26" D.Fir N.53°E., 18.6 ft. "W.C. T27S R2W S33 BT."

Rescribed 32" D.Fir N.70°W., 22.0 ft. "W.C. T27S R2W S32 BT."

Set fiberglass post and sign, 3.0 ft. West.

Cont.

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 303700

PRIMARY CORNER DESCRIPTION C C for Secs. 32 and 33 only, T27-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 21980-1 & 21989)

21980-1

The original closing cor. of secs. 32 and 33 only, on the S. bdy. of the Tp., perpetuated by Ware and Quimby in 1980, monumented with a fir, 30" dia., with healed blazes visible on north, east, and west faces, from which the remains of the original bearing trees

A fir, 29" dia., bears N.39°E., 23.1 ft., with a healed blaze. (Record, N.36°50'E.)

A roothole, bears N.63°W., 22.5 ft., with fallen fir trunk, 34" dia., lying alongside, fragmentary scribe marks visible on an unhealed blaze. (Record, N.55°40'W., 24.4 ft., rescribed by Ware and Quimby)

and a new bearing tree

A fir, 28" dia., bears N.73°W., 45.6 ft., mkd. T27S R2W S32 BT.

21989

N.0°00'01"W., bet. secs. 32 and 33. @ 7.12 feet

The witness cor. for the original closing cor. of secs. 32 and 33, established by Ware and Quimby in 1980, and is accepted as the cor.; monumented with an iron post, 2" dia., firmly set, projecting 3" above ground, with brass cap mkd.

T27S R2W

WC

CC

S

S32 | S33 ↓ 7

S4

T28S R2W

1980 RLS1005

from which a bearing tree mkd. by Ware and Quimby

A fir, 16" dia., bears S.39°E., 11.9 ft., with a healed blaze.