

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 339700

PRIMARY CORNER DESCRIPTION A P on No. Bdy. Sec. 4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882  
- (DCSO records Vol. 12 Page(s) 4865)

-----  
Set Fir post 3 ft. long, 3" sq., 24" in the ground for  
standard ¼ sec. cor. marked S C ¼ S on N. face, from which  
A Fir 8" dia., bears N.70°E., 58 lks. dist. mkd. S C ¼ S  
BT.  
A Fir 7" dia., bears N.30°E., 64 lks. dist. mkd. S C ¼ S  
BT.

GLO Resurvey by Morris Wygant, Compassman for Zachariah  
Derrick, U.S. Deputy Surveyor, Under Contract #779, dated  
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4905)

-----  
The standard ¼ sec. cor., which is a post, firmly set, mkd.  
and witnessed as described by the surveyor general. I now  
change this cor. to an Angle Point as follows:  
Cut out all marks and remark AP on N. face; then cut out all  
BTs and remark AP BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
June 1969 - C.S. File 54/40-78

-----  
Found - Orig. 8" now 36" Fir, alive, N.70°E., 38.3 ft.,  
shows good scars and fragmentary bark scribe.  
Orig. 7" now 32" Fir, alive, N.30°E., 42.2 ft. shows  
good scars.

Set brass cap at Angle Point mkd: County Surveyors Office  
T27S R2W A.P.  
T28S

1969

New BTs- 18" D.Fir S.66°W., 4.0 ft. mkd. "AP CS BT."  
14" D.Fir N.17°W., 8.7 ft. mkd. "AP CS BT."

Call of 2½ chains to ridge top West of corner fits field  
notes.