

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5461)

-----  
Set fir post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S4 on N & 9 on S face; from which  
A fir, 4" dia., bears N.43°E., 15 lks., mkd: ¼ S4 BT.  
A fir, 8" dia., bears S.45°W., 28 lks., mkd: ¼ S9 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - May 7, 1968 - C.S. File 54/26-4

-----  
Found - Orig. 8" now 23" fir, S.45°W., 18.5 ft. alive, shows good scar, we do not open.  
Orig. 4" now 18" fir, N.53°E., (rec. N.43°E. 9.9 ft) 11.9 ft. Open & find "B" scribe & reverse.

Both BTs scars face the location at which we set:  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T28S R2W  
OFFICE S 4  
1968 S 9

New BTs- 8" D.Fir N.51°W., 8.4 ft. mkd: "¼ S4 CS BT"  
Orig. 23" D.Fir S.45°W., 18.5 ft. mkd: "¼ S9 CS BT" above old scar.

Note - This corner lies on nearly level flat approx. 5 ch. E of Wolf camp & 60 ft. S of Sta. 7+87 on recently staked "P" Line.