

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 344100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4 only, T29-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Elmer F Strickler, US Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO rec Vol. 15 Pg 6237)

Set a granite stone, 18x9x6", 12" in the ground, for cor. of secs. 3 & 4, marked with 3 notches on E & W edges, from which
A Hemlock 14" dia., bears S.65°30'E., 49 lks. dist. mkd.
T29S R2W S3 BT.
A Hemlock 8" dia., bears S.17°30'W., 14 lks. dist. mkd.
T29S R2W S4 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage;
V. Perron, crew - Oct. 26, 1970 - C.S. File 54/40-198

Found - Old corner stone, in place, as called for.
Orig. 8" now 12" Hemlock, alive, S.17½°W., 9.2 ft.
we open and find "T29".

No trace of other orig. BT, due to logging.
Set Brass cap at cor. mkd: County Surveyors Office
T28S R2W
T29S S 4 | S 3
1970

Reset old stone alongside.
New BTs- 18" D.Fir S.28°W., 16.2 ft. mkd. "T29S R2W S4 CS BT"
20" Hemlock S.72½°W., 36.6 ft. mkd. "T29S R2W S4 CS
BT"

There are no trees close in Sec. 3 due to clear cut.
This corner lies approx. 300 ft. N. of logging access road,
#U.S.F.S. 2852.

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor
and Justin V Haddon, Cadastral Surveyor under Group No. 2957,
surveyed Oct./Nov. 2019 - (DCSO records Vol. 59 Page 23936)

The cor. of secs. 3 and 4 only, perpetuated by the Douglas
County Surveyor's Office, in 1970, monumented with an iron
post, 1½" dia., firmly set, projecting 7" above ground, with
a Douglas County Surveyor's Office brass cap (properly) mkd.
from which the remains of a BT reported by Strickler in 1917

A decayed hemlock stump, size indeterminate, bears
S.17½°W., 9.2 ft., no marks visible.

and a BT mkd. by the Douglas County Surveyor's Office
A hemlock, 26" dia., bears S.70¾°W., 36.2 ft., with scribe
marks T29S R2W S4 BT visible on partially healed blaze.

and a new bearing tree
A fir, 16" dia. bears S.53°E., 24.9 ft. mkd T29S R2W S3 BT
NAD 1983 (2011) LAT: 43°05'01.72"N LONG: 122°56'29.76" W